



Stocked Units

For Immediate Delivery

Pressure Transducers and Pressure Transmitters

	Model No.	Press Range	Ref	Part No	Description	Pressure Port	Electrical Termination	Output Type	Supply Voltage
 <p>GT16XX Series Click Photo To View Data Sheet</p>	GT1600	15	psig	GT1600-15G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	25	psig	GT1600-25G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	50	psig	GT1600-50G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	100	psig	GT1600-100G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	200	psig	GT1600-200G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	500	psig	GT1600-500G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	1000	psig	GT1600-1000G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	3000	psig	GT1600-3000G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	5000	psig	GT1600-5000G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1600	10000	psig	GT1600-10000G-000	0.1% Accuracy, 0-5 VDC Output	1/4 NPT Female	PT1H-10-6P	Isolated	14-32
	GT1650	15	psig	GT1650-15G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	25	psig	GT1650-25G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	50	psig	GT1650-50G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	100	psig	GT1650-100G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	200	psig	GT1650-200G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	500	psig	GT1650-500G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	1000	psig	GT1650-1000G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	3000	psig	GT1650-3000G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	5000	psig	GT1650-5000G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
	GT1650	10000	psig	GT1650-10000G-000	0.1% Accuracy, 4-20 mA Output	1/4 NPT Female	PT1H-10-6P	Current	9-36
 <p>GT18XX Series Click Photo To View Data Sheet</p>	GT1800	15	psig	GT1800-15G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	25	psig	GT1800-25G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	50	psig	GT1800-50G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	100	psig	GT1800-100G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	200	psig	GT1800-200G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	500	psig	GT1800-500G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	1000	psig	GT1800-1000G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	3000	psig	GT1800-3000G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	5000	psig	GT1800-5000G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1800	10000	psig	GT1800-10000G-000	0.25% Accuracy, 0-5 VDC Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Isolated	14-32
	GT1850	15	psig	GT1850-15G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	25	psig	GT1850-25G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	50	psig	GT1850-50G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	100	psig	GT1850-100G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	200	psig	GT1850-200G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	500	psig	GT1850-500G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	1000	psig	GT1850-1000G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	3000	psig	GT1850-3000G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	5000	psig	GT1850-5000G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36
	GT1850	10000	psig	GT1850-10000G-000	0.25% Accuracy, 4-20 mA Output	1/4 NPT Male	PVC Cable w/ Strain Relief	Current	9-36

Find More Information at:
stellartech.com

Due to the nature of technology, changes are inevitable. For latest technical specifications, see our website.

237 Commerce Drive • Amherst, NY 14228 • USA
Tel: 716.250.1900 • **Fax:** 716.250.1909
Email: info@stellartech.com