

Series GT25XX

Hazardous Location Pressure Transmitters



Description

The GT25XX Series Transmitter incorporates a flameproof/explosion-proof housing which allows the use of both our analog & digital electronics. This versatility allows STI to utilize its years of electronic development to provide "Application-Solutions" for years of service in demanding environments.

STI utilizes rugged, reliable bonded foil strain gage technology providing both an accurate and stable unit. Our stainless steel construction provides these units with the capability of withstanding harsh environments yet providing high accuracy with low susceptibility to shock & vibration.

"Application-Solutions" we provide include the following:

- Inconel construction for H₂S or saltwater service
- Dual pressure and temperature outputs
- PC/PDA compatibilities
- OEM Customization

The brief specifications listed on the back are but a few of the more important parameters of interest; make sure to contact the sales office closest to you for further definition. In most cases, independent data sheets support these applications and provide additional information.

Standard Features

- Explosion Proof - USA/CAN
CSA/US CLI Div 1&2, Groups A,B,C,D
- Rugged Strain Gage Technology
- Reliable Long Term Stability
- Stainless Steel Construction
- Low Sensitivity to Shock & Vibration
- Analog or Digital Electronics

Optional Features

- Total Error Band Accuracy
Including Temperature
- Customer Specified Pressure Port
- Alternate Materials of Construction
- Magnetic Zero
- Non-Incendive USA/CAN
CSA CLI Div 2 Groups A,B,C,D
- Intrinsically Safe - USA/CAN
CSA CLI Div 1&2, Groups A,B,C,D

GT25XX

Series GT25XX Specifications

Baseline Configuration Specs Represented.
Modifications Encouraged - See Below
Custom Designs Available

Performance

Static Accuracy

± 0.25% FSO by BFSL or
± 0.1% FSO by BFSL (optional).

Resolution

Analog - Infinite.
Digital - .025% FSO.

Thermal Shift

< ± 0.020% FSO/°F typical.
< ± 0.005% FSO/°F optional.

Insulation Resistance

> 100 megohms at 50 Vdc at 70°F.

Zero Balance

± 1% FSO at 70°F.

Span

± 1% FSO at 70°F.

Frequency Response

Consult Factory.

Mechanical Characteristics

Standard Ranges

0 - 5, 10, 25, 30, 50, 75, 100, 200, 500,
750, 1000, 1500, 2000, 3000, 5000,
7500, 10000, 15000, 20000, 25000 and
30000 PSIA / PSIG / PSID.

Proof Pressure

1.5 times FSO range minimum.
1500 PSI for differential units.

Burst Pressure

2.0 times FSO range minimum.
3000 PSI for differential.

Operating Media

Fluids and gases compatible with stainless
steel. Inconel and other materials optional.

Enclosure

Body of stainless steel.

Pressure Fitting

1/4" NPT Male (standard) or Female.
7/16"-20 per MS33649-4 (Female).
7/16"-20 per MS33656-4 (Male).
AE F250-C, 9/16-18 UNF for
ranges 15,000 PSI & up.
1502, 2202 hammer union.

Weight

Approx. 16 ounces for gage units.
Approx. 60 ounces for differential units.

Electrical Characteristics

ANALOG OUTPUTS

Excitation

4-20mA Current Loop:
2-wire 9-36 Vdc unregulated.
3-wire 14-40 Vdc unregulated.
Isolated Voltage Output:
8-18 Vdc or 14-32 Vdc unregulated.
Non-Isolated Voltage Output:
8-40 Vdc unregulated.
3 or 4 wire available.

DIGITAL OUTPUTS

Excitation

RS-232, RS-485, CANbus
8-30 Vdc unregulated.

Programming

PC.

COMMON

Electrical Connection

1/2" NPT Male (standard) or Female
conduit fitting with Teflon cable (standard),
vented polyurethane or rubber cable
(optional). 2 ft. of cable supplied as
standard. Longer lengths available
upon request.

Electrical Protection

- EMI/RFI protected.
- Surge protection to 500 Vdc.
- Reverse polarity protected.
- Short circuit protected

Environmental Characteristics

Compensated Temperature Range

+30°F to +130°F.
Options Available..

Operating Temperature Range

-40°F to +185°F.

Dimensions (inches)

Dimensional data not shown due to number
of models available. Consult factory.

MODEL IDENTIFICATION

G	T	2	5	X	X
SERIES		ANALOG OUTPUT		DIGITAL OUTPUT	
		0 = Volts 5 = 2-wire Loop 6 = 3-wire Loop 1 = None		0 = None 1 = RS-485 2 = RS-232 4 = CANbus	

Certification / Rating

Hazardous Location Certification

CSA Rated
Explosion Proof Class I, Division 1,
Groups A,B,C,D
Non-Incendive Class I, Division 2,
Groups A,B,C,D
(Non-Incendive devices require
conduit termination)

Applied Standards
CSA STD C22.2 NO. 142M1987
CSA STD C22.2 NO. 30M1986
UL STD - 1203
UL STD - 1604



MODIFICATIONS: We realize transducer applications vary greatly and as such our designs are flexible. Choice of pressure port, electrical termination, material compatibility and performance characteristics are a few of the many options available. Specifications on this datasheet represent the standard configuration only. Product and company names listed are trademarks of their respective companies. Specifications subject to change without notice.

WARRANTY: Stellar Technology warrants that its product shall be free from defective workmanship and/or material for a twelve month period from the date of shipment, provided that Stellar Technology's obligation hereunder shall be limited to correcting any defective material FOB our factory. No allowance will be made for any expenses incurred for correcting any defective workmanship and/or material without written consent by Stellar Technology. This warranty is in lieu of all other warranties expressed or implied.

Find More Information at:
stellartech.com

Due to the nature of technology, changes are inevitable. For latest technical specifications, see our website.

237 Commerce Drive • Amherst, NY 14228 • USA

Tel: 716.250.1900 • Fax: 716.250.1909

Email: info@stellartech.com

ISO 9001:2000

