



Series AP5101

DIN-Rail Amplifier for Strain Gage Transducers



Description

The AP5101 Series is a DIN-rail mounted single channel DC amplifier designed to provide variable excitation and signal conditioning for Stellar Technology's strain gaged, mV/V, pressure transducers, load cells, force sensors, and reaction torque sensors. This DIN-rail amplifier provides up to 10V output or 4-20 mA output with transducer signals from 10 mV to 10V. This amplifier accepts both uni-polar or bi-polar input signals and can produce corresponding uni-polar and bi-polar voltage outputs. Current outputs are uni-polar. The AP5101 incorporates a DC-DC converter that ensures the output of the unit is electrically isolated from the supply. The DIN-rail housing is constructed of a high-impact thermoplastics case with recessed screw-clamp terminals for all connections and a 25-turn zero and fine gain adjustment accessible from the front panel. A push switch and the capability to connect remotely to an internal shunt calibration resistor are also located on the front panel. Excitation, coarse gain and switches to filter the output, are internal and easily accessible by disengaging the front panel and board assembly from the housing.

Standard Features

- Standard DIN-rail Package
- Voltage and Current Output
- Accepts Most Full Bridge Strain Gage Transducers
- Input/Output Isolation
- Broad Range of Inputs (4mV to 10V)
- Selectable Transducer Bridge Excitation of 3-10 Vdc
- Accepts Both Uni-Polar and Bi-Polar Inputs
- Zero and Fine Gain Adjust From Front Panel
- Remote Shunt Calibration From Front Panel
- Internal Coarse Gain Easily Accessible
- Internal Filters Easily Accessible
- Bridge Completion Capable

Series AP5101

Specifications

Baseline Configuration Specs Represented.
Modifications Encouraged - See Below
Custom Designs Available

Performance

Linearity

0.02% of FSO.

Bandwidth

5kHz typical as standard or 500 Hz or 20 Hz with filters ON.

Noise

5mV or 20 μ A rms (less with filter ON) typical.

Zero Adjustment

\pm 2V (or 0-10mA) output typical.
Depends on Fine Gain setting.

Sensitivity Range

4mV – 10V input for 5V (or 20mA) output in 6 ranges with 4:1.

Fine Gain Control

Gain range x1 to x1250.

Shunt Calibration

Push switch operation or R.Cal.
Connection to R.Cal common connects 59k via relay. Relay current 10mA.

Mechanical Characteristics

Configuration

DIN-rail mounting.

Material of Construction

Durable thermoplastics enclosure.

Weight

Approximately 4.6 oz.

Seals

IP20 Specification. (NEMA ventilated)

Dimensions

4.51" deep x 0.89" wide x 3.90" high

Electrical Characteristics

Supply Voltage

9 to 36V dc.

Supply Current

120mA typical with 24V supply,
10V excitation and 350 ohm bridge.
(80-250mA depending on supply,
excitation & bridge resistance.)

Analog Outputs

0-10Vdc, 5mA (isolated).
 \pm 10Vdc, 5mA (isolated).
4-20mA (isolated).
(Loop resistance 100 ohm - 500 ohm)

Transducer Excitation

3 to 10V (user selectable), 100mA max.

Regulation

Excitation change = 0.10% typical with
load change 0-100 mA.

Input Impedance

>10M ohm.

Environmental Characteristics

Operating Temperature Range

+14 to +140°F.

Temperature Coefficient

\pm 0.003% F.S./°F minimum.
(Combined zero and span)

EMC Specification

When subjected to radiated
electromagnetic energy (as IEC 801-3)
an additional error can occur at certain
frequencies:

Field Strength	Typical Maximum Error
10V/m	5%
3V/m	0.5%

Connections

Supply and output connection are made
by 4 x 4-way screw-clamp terminals.

- 1 Excitation Hi
- 2 Excitation Lo
- 3 Signal Hi
- 4 Signal Lo
- 5 Screen
- 6 R. Cal com
- 7 R. Cal
- 8 CAL
- 9 Volts Out
- 10 Common
- 11 Common
- 12 Current Out
- 13 Supply +
- 14 Supply –
- 15 Screen
- 16 N/C



Modifications and Warranty

MODIFICATIONS: We realize transducer applications vary greatly and as such our designs are flexible. Choice of pressure port, electrical termination, material compatibility and performance characteristics are a few of the many options available. Specifications on this datasheet represent the standard configuration only. Product and company names listed are trademarks of their respective companies. Specifications subject to change without notice.

WARRANTY: Stellar Technology warrants that its product shall be free from defective workmanship and/or material for a twelve month period from the date of shipment, provided that Stellar Technology's obligation hereunder shall be limited to correcting any defective material FOB our factory. No allowance will be made for any expenses incurred for correcting any defective workmanship and/or material without written consent by Stellar Technology. This warranty is in lieu of all other warranties expressed or implied.



ISO 9001/AS9100

Due to the nature of technology, changes are inevitable. For latest technical specifications, see our website.

237 Commerce Drive • Amherst, NY 14228 • USA

Tel: 716.250.1900 • Fax: 716.250.1909

Web: stellartech.com • Email: info@stellartech.com

Copyright © 2015 STI • All Rights Reserved
Datasheet P/N: 234188C DCN 13447